



**RB455A Utility Baler – Next Generation Variable Chamber Round Baler**

<b>BALE SIZE</b>	
Bale diameter, in (mm)	36 (915) - 60 (1524)
Bale width, in (mm)	46.5 (1182)
Bale weight, lb (kg)	1,000 (454)
<b>BALER DIMENSIONS AND WEIGHT</b>	
Overall length, gate closed, in (mm)	163 (4134)
Overall width, in (mm)	85 (2162)
Overall height, gate closed, in (mm)	100 (2534)
Weight, lb (kg)	3,460 (1,569)
<b>BALE FORMING</b>	
Number of forming belts	5
Type of belts	Chevron
Belt width, in (mm)	7 (178)
Belt length, in (mm)	343 (8712)
Number of rolls, total	14
Tensioning method	1 extension spring; 1 hydraulic cylinder
<b>BALE EJECTOR</b>	
Bale ramp	Optional
<b>STANDARD PICK UP</b>	
Feeder type	Standard
Overall width, in (mm)	62 (1554)
Width between outside tines, in (mm)	45 (1134)
Tine spacing, in (mm)	2.62 (67)
Number of tine bars	4
Number of tines	72
Number of windguard fingers	9
Pickup drive	Chain
Pickup drive protection	Breakaway Chain
Pick up wheel	Optional
<b>WRAPPING SYSTEM</b>	
Twine system type	Electric - Center Pivot - Dual Arms
Twine system control	Automatic, Electric
Number of twine balls	4
Netwrap option	Optional
<b>MAIN DRIVE</b>	
Standard main drive protection	Shear bolt
PTO, rated rpm	540
PTO Category rating	4
<b>TRACTOR REQUIREMENT</b>	
Minimum tractor PTO hp (kW)	40 (30)
Minimum number of hydraulic remotes	1 to 2
<b>MONITORING</b>	
Twine wrap monitor	Optional
Net wrap monitor	Optional
<b>TIRE SIZE</b>	
Standard baler tire size	11L -154
Optional baler tire size	31 × 13.5 - 15



**Safety Never Hurts!™** Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

Case IH is a registered trademark of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.

Availability of some models and equipment builds vary according to the country in which the equipment is used.

