

RRX SERIES REAR-MOUNT ROTARY FINISHING MOWER Specifications



Models RRX160 & RRX172

MODEL	RRX160	RRX172
TRACTOR COMPATIBILITY	Under 40 PTO hp (29.8 kW) w/ 540 rpm PTO and Cat. I 3-pt. hitch	Under 40 PTO hp (29.8 kW) w/ 540 rpm PTO and Cat. I 3-pt. hitch
Cutting Width	60 in. (152 cm)	72 in. (183 cm)
Deck Design	Air Tunnel	Air Tunnel
Deck Construction	Fabricated	Fabricated
Drive Type	Shaft & gear box drive	Shaft & gear box drive
Drive Method	Rear 540 rpm PTO	Rear 540 rpm PTO
Gear Box Rating	40 hp (29.8 kW)	40 hp (29.8 kW)
Blade Drive	V-belt	V-belt
Number of Blades	3	3
Cutting Height	1 to 5.5 in. (2.5 to 14 cm)	1 to 5.5 in. (2.5 to 14 cm)
Spindle Diameter	1 in. (2.5 cm)	1 in. (2.5 cm)
Spindle Housing	Cast iron	Cast iron
Spindle Lube	Top greasable	Top greasable
Pulley Material	Cast iron	Cast iron
Discharge	Right	Right
Hitch	Cat. I 3-pt.	Cat. I 3-pt.
Number of Gauge Wheels	4	4

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

© 2007 CNH America LLC. All rights reserved. www.caseih.com/na

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.



SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.