



FOR OVER 30 YEARS, CUSTOMERS HAVE COME TO EXPECT GREAT PERFORMANCE OUT OF THEIR AXIAL-FLOW® COMBINES, AND THE SAME GOES FOR CASE IH HEADS. HEADERS PLAY AN IMPORTANT ROLE IN HARVESTING, AND CASE IH HAS IMPROVED, EXPANDED, AND ENHANCED THE HEADER LINEUP TO PROVIDE THE LATEST IN HARVESTING TECHNOLOGY.



FOR THOSE WHO DEMAND MORE

THE LARGEST SELECTION OF PRODUCTIVITY-ENHANCING HEADERS.

1010 & 1020 GRAIN AND FLEX HEADS

The Case IH 1000 Series grain headers have a proven record of optimal performance in a variety of crops and conditions. The 1010 header can't be beat for wheat, milo, flax, barley, oats, and many other crops. With a selection of options and standard equipment to choose from, these headers are proven performers. Choose from 20-ft. (less cutting equipment) to 30-ft. sizes with options for cutterbars and header controls. Hydraulic reel lift and hydraulic reel drive are standard equipment. The Case IH cutterbar header is designed to reduce the loss at the cutterbar to approximately 3 percent — that puts you bushels ahead of your competitors. Case IH 1020 grain heads are designed and engineered to cut low and flex with the terrain — this makes your harvesting job easier and more productive.

2010 & 2020 GRAIN AND FLEX HEADS

The Case IH 2000 Series grain headers offer enhanced floor profiles and feeding characteristics that provide smoother crop flow and reduced wear. Full-fingered augers ensure consistent crop feeding even in adverse field conditions. 2010 and 2020 headers feature a large 26-inch diameter auger, stainless steel auger trough, and a single lever header attachment.

2162 FLEX-DRAPER

The Case IH 2162 Flex-Draper is designed with the large producer in mind. The 2162 offers a new center-mount design, a high center opening and new flexible linkage for softer ground pressure and better feeding. With its large capacity inboard mounted motors and sealed draper bearings, the 2162 is the next evolution in grain harvesting headers.

2142 & 2152 RIGID DRAPER HEADS

Case IH draper headers are designed to match crop types, yields and combine capacities. A wide range of cutting widths, matched draper delivery openings and variable draper speeds together provide uniform crop flow into the combine. Adjustable guard angle allows for unmatched performance in different crop types and terrain. Self-tracking drapers, with a special tightener system, enable full-length draper alignment. Case IH draper headers are used in a wide variety of crops and conditions around the world. These machines have years of proven experience in wheat, mustard, canola, barley, lentils, lupins, oats, peas, milo, flax, grass seeds, pinto beans, safflower, alfalfa, millet, soybeans, rice and sunflowers (Special attachments may be required).

2200 & 2400 CORN HEADS

Case IH corn heads provide the best harvesting technology you can buy. The larger diameter cantilevered stalk rolls are designed to offer greater capacity and faster harvest speeds. Take a look at the low profile dividers and you'll see how they effectively hug the ground — resulting in more ears in the header for increased efficiency and productivity. Available in 6-, 8- or 12-row configurations with various row spacing options, the 2200 and 2400 Series corn heads deliver powerful performance and superior reliability for the highest quality corn harvesting you can find.



2600 CHOPPING CORN HEAD

Case IH chopping corn heads offer a proven, highly efficient alternative to cornstalk residue management. The larger diameter stalk rolls are designed to offer greater capacity and force the stalks into the stalk chopper, this allows faster harvest speeds. The Case IH chopping corn heads also offer an independent gear box for each

row, which gives the operator the ability to switch the chopping mechanism on or off independently of the rest of the corn head. With 4 different configurations, 6-, 8-, 12-row and even an 8-row folding version, you soon see how innovation has driven the new leader in the chopping corn head industry.

1010/1020 AUGER HEADER FEATURES:

- 23.6 in. (600 mm) diameter floating auger
- Optional full width retracting fingers
- Hydraulic drive reel
- Oil bath knife box
- Super Sta-Sharp™ knife sections
- Heavy-duty knife guards
- Tethered knife drive shield

2010/2020 AUGER HEADER FEATURES:

- 26 in. (660 mm) diameter floating auger
- Full width retracting fingers
- Stainless steel auger trough
- Single lever hydraulic hook-up
- Super Sta-Sharp™ knife sections
- Heavy-duty knife guards
- Hinged knife drive shield
- 2020 offers 4.5 in. of flex

2015 & 2016 PICKUP HEADS

Designed with the strict requirements of the large grain producer in mind, the Case IH belt and rake-up line of pickup headers offer a unique solution in grain harvesting. This header is made to work in various

crops and diverse harvesting conditions. If you are harvesting cereal grains, beans, peas, lentils or canola, you can be confident that the 2015 and 2016 pickup header will meet and exceed your expectations.

2142/2152/2162 DRAPER FEATURES:

- Flex-linkage on 2162 for softer ground pressure
- Center-mount design
- High center opening for unobstructed crop flow
- New hydraulic knife drive to optimize ground speeds
- Large-capacity inboard mounted motors
- Sealed draper roller bearings
- Reversible drapers with V-guide tracking



2200/2400 CORN HEAD FEATURES:

- Two-piece cantilevered stalk rolls
- Optional straight fluted stalk rolls
- Chrome pin gathering chains
- Standard hydraulic stripper plate adjustment
- Low profile polyethylene row unit hoods and dividers
- Divider height adjustment
- Larger 16 in. (406 mm) diameter auger
- Two-speed main drive (2200 Series)
- Cast iron row unit gearbox

2600 CHOPPING CORN HEAD FEATURES:

- Two blade horizontal chopping mechanism
- Independent chopper gearbox drives on each row unit
- Ability to disengage chopping mechanism of each row independently
- One-piece rod for manual disengagement of the chopper
- Hydraulic stripper plate adjustment
- Low-profile polyethylene row unit hoods and dividers



2015/2016 PICK-UP HEAD FEATURES:

- Optional hydraulic crop hold down
- 24 in. diameter floating auger
- Variable speed hydraulic drive
- Two-stage delivery unit
- Center-balanced shock-absorbing pickup suspension



		Axial-Flow 2577 & 2588	Axial-Flow 7010 & 8010
Corn Heads			
6 Row Configurations 27.5" - 38" Spacing	27.5"	2206	
	30"	2206/2606	
	36"	2206	
	38"	2206	
8 Row Configurations 22" - 38" Spacing	22"	2208	2408
	27.5"	2208	2408
	30"	2208/2608	2408/2608
	36"	2208	2408
12 Row Configurations 20" - 30" Spacing	38"	2208	2408
	20"	2212 - 2588 only	2412
	22"	2212 - 2588 only	2412
	30"	2212 - 2588 only	2412/2612
Grain Heads			
Rigid Configurations 20' - 30' Cutting Width	20'	1010	2010
	25'	1010	2010
	30'	1010	2010
Standard Flex 20' - 35' Cutting Width	20'	1020	2020
	22.5'	1020	
	25'	1020	2020
	30'	1020	2020
Full-Fingered Flex 20' - 35' Cutting Width	35'		2020
	20'		2020
	25'	1020	2020
	30'	1020	2020
	35'		2020
Draper Heads			
Standard Rigid Configurations 20' - 35' Cutting Width	20'	2142	2142
	30'	2142	2142
	35'	2142	2142
Heavy Duty Rigid Configurations 25' - 40' Cutting Width	25'	2152	2152
	30'	2152	2152
	35'	2152	2152
	40'		2152
Flex Configurations 30' - 40' Cutting Width	30'	2162	2162
	35'	2162	2162
	40'		2162
Pick-Up Headers			
Rake-Up Configurations 14' - 16' Configurations	14'	2015	2016
	16'	2015	2016
Belt-Type Configurations 14' - 16' Configurations	14'	2015	2016
	16'	2015	2016

GRAIN HEADERS	1010	1020	2010	2020	2142	2152	2162
Description	Rigid Auger Header	Flexible Auger Header	Rigid Auger Header	Flexible Auger Header	Rigid Draper Header	Rigid Draper Header	Flexible Draper Header
Cutter Bar							
Cutting Widths - ft. (m)	20, 25, 30 (6.1, 7.62, 9.14)	20, 22.5, 25, 30 (6.1, 6.8, 7.62, 9.14)	20, 25, 30 (6.1, 7.62, 9.14)	20, 25, 30, 35 (6.1, 7.62, 9.14, 10.6)	25, 30, 35 (7.6, 9.14, 10.6)	25, 30, 35, 40 (7.62, 9.14, 10.6, 12.2)	30, 35, 40 (9.14, 10.6, 12.2)
Weight - approx. lbs (kg)							
20 (6.1m) / 21 ft. (6.4 m)	2,771 (1257)	3,784 (1716)	3,100 (1406)	4,035 (1830)	NA	NA	NA
22.5 (6.8m)	N/A	4,235 (1921)	N/A	N/A	NA	NA	NA
25 ft. (7. m)	3,341 (1516)	4,530 (2055)	4,040 (1833)	4,658 (2113)	5272 (2391)	5,596 (2538)	NA
30 ft. (9.1 m)	4,277 (1940)	5,281 (2395)	4,756 (2157)	5,630 (2554)	5,967 (2706)	6,672 (2981)	6,648 (3015)
35 (10.6m)	N/A	N/A	N/A	6,940 (3148)	6,444 (2923)	6,849 (3106)	7,061 (3202)
40 ft. (12.2 m)	N/A	N/A	N/A	N/A	NA	7,285 (3282)	7,475 (3910)
Auger							
Diameter - in. (mm)	23.625 (600)	23.625 (600)	26 (660)	26 (660)	Upr Cross - 12 (305) Feed - 22 (356)	Upr Cross - 12 (305) Feed - 22 (356)	Upr Cross - 12 (305) Feed - 22 (356)
Speed - RPM	Std. 152/Opt. 170	Std. 152/Opt. 170	Std. 158/Opt. 139	Std. 158/Opt. 139	Cross - 0-464/Feed - 150	Cross - 0-464/Feed - 150	Cross - 0-464/Feed - 150
Full Fingered	Opt. 25, 30 ft.	Opt. 25, 30 ft.	Std. 25 and 30 ft.	Std. 25, 30 and 35 ft.	N/A	N/A	N/A
Reel							
Reel	5	NA	NA	NA	NA	NA	NA
Pickup Reel (Tines)	6 (Plastic)	6 (Plastic)	6 (Steel for rice, Plastic std.)	6 (Plastic)	5 bat plastic fingers, single span	5 or 6 bat plastic or steel fingers	5 or 6 bat plastic or steel, split span
Diameter - in. (mm)	42 (1067)	42.4 (1077)	40 (1016)	42 (1067)	65 (1651)	65 (1651)	65 (1651)
Drive - RPM	Hydraulic / 10 to 84 RPM	Hydraulic / 10 to 84 RPM	Hydraulic / 5 to 61 RPM	Hydraulic / 5 to 61 RPM	Hydraulic / 10 to 64 RPM	Hydraulic / 10 to 64 RPM	Hydraulic / 10 to 64 RPM
Sickle/Knife							
Type	Overserrated "Sta-Sharp" / "Super Sta-Sharp"	Overserrated "Sta-Sharp" / "Super Sta-Sharp"	Overserrated "Sta-Sharp" / "Super Sta-Sharp"	Overserrated "Sta-Sharp" / "Super Sta-Sharp"	Overserrated, bolt sections	Overserrated, bolt sections	Overserrated, bolt sections
Drive	Section to wobble box	Section to wobble box	Section to wobble box	Section to wobble box	Enclosed oil bath wobble box	Enclosed oil bath wobble box	Enclosed oil bath wobble box
Knife - in. (mm)	Std. 3 (76.2)	Std. 3 (76.2)	Std. 3 (76.2)	Std. 3 (76.2)	3 (76.2)	3 (76.2)	4 (76.2)

CORN HEADERS	2206	2208/2408	2212/2412	2606	2608	2608F	2612
General							
Number of rows	6	8	12	6	8	8	12
Row spacing - in. (mm)	30, 36, 38 (762, 914, 965)	22, 30, 36, 38 (559, 762, 914, 965)	20, 22, 30 (508, 559, 762)	30 (762)	30 (762)	30 (762)	30 (762)
Number of gathering chains	12	16	24	12	16	16	24
Divider type	Poly	Poly	Poly	Poly	Poly	Poly	Poly
Overall Dimensions							
Width (Max. row spacing)							
20 in. (508 mm)	N/A	N/A	20 ft. 10 in. (6350 mm)	N/A	N/A	N/A	N/A
22 in. (559 mm)	N/A	15 ft. 6 in. (4724 mm)	22 ft. 10 in. (6960 mm)	N/A	N/A	N/A	N/A
30 in. (762 mm)	15 ft. 10 in. (4824 mm)	20 ft. 10 in. (6356 mm)	30 ft. 10 in. (9404 mm)	15 ft. 7 in. (4790)	20 ft. 10 in. (6390)	20 ft. 10 in. (6390) Open/ 10 ft. 8 in. (3300) Closed	—
36 in. (914 mm)	18 ft. 6 in. (5645 mm)	24 ft. 8 in. (7511 mm)	N/A	N/A	N/A	N/A	N/A
38 in. (965 mm)	19 ft. 2 in. (5848 mm)	25 ft. 6 in. (7778 mm)	N/A	N/A	N/A	N/A	N/A
Height (level ground)	3 ft. 11 in. (1197 mm)	3 ft. 11 in. (1197 mm)	3 ft. 11 in. (1197 mm)	4 ft. (1220 mm)	4 ft. (1220 mm)	4 ft. (1220 mm) Open/ 9 ft. 6 in. (2900 mm) Closed	4 ft. (1220 mm)
Length with dividers	10 ft. 4 in. (3158 mm)	10 ft. 4 in. (3158 mm)	10 ft. 4 in. (3158 mm)	9 ft. 6 in. (2900 mm)	9 ft. 6 in. (2900 mm)	6 ft. 5 in. (1980 mm) Closed 9 ft. 6 in. (2900 mm) 9 ft. 5 in. (2870 mm)	9 ft. 6 in. (2900 mm) 10 ft. 5 in. (3175 mm)
Length without dividers	7 ft. 4 in. (2234 mm)	7 ft. 4 in. (2234 mm)	7 ft. 4 in. (2234 mm)	7 ft. 5 in. (2260 mm)	8 ft. 5 in. (2565 mm)		
Weight: Approx. - lbs. (kg)							
20 in. (508 mm)	N/A	N/A	7,045 (3196)	N/A	N/A	N/A	N/A
22 in. (559 mm)	N/A	4,870 (2209)	7,550 (3298)	N/A	N/A	N/A	N/A
30 in. (762 mm)	4,105 (1889)	5,700 (2585)	8,390 (3742)	4,431 (2010)	5,732 (2600)	6,085 (2760)	8,598 (3900)
36 in. (914 mm)	4,680 (2168)	6,235 (2828)	N/A	N/A	N/A	N/A	N/A
38 in. (965 mm)	4,680 (2168)	6,235 (2828)	N/A	N/A	N/A	N/A	N/A
Knife stalk rolls	Std. with reversible knife sections	Std. with reversible knife sections	Std. with reversible knife sections	Standard	Standard	Standard	Standard
Number of knives per roll	4 - Double edge	4 - Double edge	4 - Double edge	4 - Single edge	4 - Single edge	4 - Single edge	4 - Single edge
Weed knives - front and rear	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
Row unit drive	Enclosed in gearbox	Enclosed in gearbox	Enclosed in gearbox	Enclosed in gearbox	Enclosed in gearbox	Enclosed in gearbox	Enclosed in gearbox
Head speed	525 RPM	525 RPM	525 RPM	575 RPM	575 RPM	575 RPM	575 RPM
Speed ranges	2 - Direct/overdrive	2 - Direct/overdrive	2 - Direct/overdrive	—	—	—	—
Stripper plates	Hydraulic adjustable	Hydraulic adjustable	Hydraulic adjustable	Hydraulic adjustable	Hydraulic adjustable	Hydraulic adjustable	Hydraulic adjustable
Automatic front height control	Optional/pre-wired	Optional/pre-wired	Optional/pre-wired	Optional/pre-wired	Optional/pre-wired	Optional/pre-wired	Optional/pre-wired
Stalk Chopper Blade RPM	N/A	N/A	N/A	2880	2880	2880	2880

PICKUP HEADERS	2015	2016
Actual Pickup Widths - ft. (m)	14 (4.27)	14, 16 (4.27, 4.87)
Floating Auger		
Diameter - in. (mm)	24 (607)	24 (607)
Speed - RPM (Opt)	188 (160)	188 (160)
Reel		
Drive - RPM	Hydraulic	Hydraulic
Reel Lift & Fore/Aft	Hydraulic	Hydraulic
Weight		
With Belt Pickup		
14 ft. (4.27 m) width - lbs. (kg)	3,200 (1451)	3,200, 3,400 (1451, 1542)
With Rake Pickup		
14 ft. (4.27 m) width - lbs. (kg)	3,200 (1451)	3,200, 3,400 (1451, 1542)
Draper Belts - 19 in. (48.3 cm)		
14 ft. (4.27 m) width	8	8, 10
Overall Width to Tire Edges		
Belt Pickup - 14 ft. - in. (m)	168 (4.27)	168 (4.27)
Rake Pickup - 14 ft. - in. (m)	196 (5.0)	196 (5)
Belt Pickup - 16 ft. - in. (m)	N/A	192 (4.89)
Rake Pickup - 16 ft. - in. (m)	N/A	216 (5.5)



Safety Never Hurts!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

Case IH is a registered trademark of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.

Availability of some models and equipment builds varies according to the country in which the equipment is used.

