

# GRAIN & FLEX HEAD Specifications



## Models 2010 & 2020

MODELS	2010	2020
<b>Description</b>	<b>Rigid Auger Header</b>	<b>Flexible Auger Header</b>
<b>CUTTER BAR</b>		
Cutting Widths – ft. (m)	20, 25, 30 (6.1, 7.62, 9.14)	20, 25, 30, 35 (6.1, 7.62, 9.14, 10.6)
<b>WEIGHT – APPROX. LBS (KG)</b>		
20 (6.1m) / 21 ft. (6.4 m)	3,100 (1406)	4,035 (1830)
22.5 (6.8m)	N/A	N/A
25 ft. (7. m)	4,040 (1833)	4,658 (2113)
30 ft. (9.1 m)	4,756 (2157)	5,630 (2554)
35 (10.6m)	N/A	6,940 (3148)
<b>AUGER</b>		
Diameter – in. (mm)	26 (660)	26 (660)
Speed – RPM	Std. 158/Opt. 139	Std. 158/Opt. 139
Full Fingered	Std. 25 and 30 ft.	Std. 25, 30 and 35 ft.
<b>REEL</b>		
Reel	N/A	N/A
Pickup Reel (Tines)	6 (Steel for rice, Plastic std.)	6 (Plastic)
Diameter – in. (mm)	40 (1016)	42 (1067)
Drive – RPM	Hydraulic / 5 to 61 RPM	Hydraulic / 5 to 61 RPM
<b>SICKLE/KNIFE</b>		
Type	Overserrated “Sta-Sharp”/ “Super Sta-Sharp”	Overserrated “Sta-Sharp”/ “Super Sta-Sharp”
Drive	Section to wobble box	Section to wobble box
Knife - in. (mm)	Std. 3 (76.2)	Std. 3 (76.2)

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

© 2009 CNH America LLC. All rights reserved. [www.caseih.com/na](http://www.caseih.com/na)

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.



**SAFETY NEVER HURTS!™** Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.