

PICK-UP HEAD Specifications

Models 2016

MODELS	2016
Actual Pickup Widths – ft. (m)	14, 16 (4.27, 4.87)
FLOATING AUGER	
Diameter – in. (mm)	24 (607)
Speed - RPM (Opt)	188 (160)
PICK-UP	
Drive	Hydraulic
Wind Guard Lift	Hydraulic
WEIGHT	
With Belt Pickup	
14 ft. (4.27 m) width – lbs. (kg)	3,200 (1451)
16 ft. (4.9m) width-lbs (kg)	3,400 (1542)
With Rake Pickup	
14 ft. (4.27 m) width – lbs. (kg)	3,200 (1451)
16 ft. (4.9m) width-lbs (kg)	3,400 (1542)
Draper Belts – 19 in. (48.3 cm)	
14 ft. (4.27 m) width	8
16 ft. (4.9m) width	10
OVERALL WIDTH TO TIRE EDGES	
Belt Pickup – 14 ft. – in. (m)	168 (4.27)
Rake Pickup – 14 ft. – in. (m)	196 (5.0)
Belt Pickup – 16 ft. – in. (m)	192 (4.89)
Rake Pickup – 16 ft. – in. (m)	216 (5.5)

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

© 2009 CNH America LLC. All rights reserved. www.caseih.com/na

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.



SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.