

# TD102 PULL-TYPE DISC MOWER Specifications



## Model TD102

MODEL	TD102
<b>CUTTER BAR</b>	
Cutting width	10 ft. 4 in. (3.16 m)
Cutting height	0.95 - 3.2 in. (24 - 81 mm)
Cutting height w/opt. high-stubble shoes	2.25 - 4.5 in. (58 - 115 mm)
Type cutterbar	Modular
Number of discs/knives per disc	8/2
Disc speed @ rated PTO speed	2835 rpm
Cutter bar shear protection	Standard – Frangible splines in disc drive hub
Cutter bar flotation	Vertical and lateral, adjustable springs
Swath width	95 in. (2.4 m)
<b>DRIVELINE</b>	
Input speed	540 rpm
Driveline protection	Slip clutch and overrunning clutch assembly @ rear of PTO shaft
<b>TRACTOR REQUIREMENTS</b>	
Minimum PTO power required	60 hp (45 kW)
PTO Splines/Diameter	6-Splines/1-3/8 in. (35 mm)
Hydraulic circuits required	2
Minimum relief pressure required	1500 psi (103 bar)
Drawbar requirements – ASAE	ASAE Category II drawbar
<b>TIRES</b>	
Tubeless Ag rib implement tires	27x9.5-15 6PR
Max. transport speed	20 mph (32.2 kph)
<b>DIMENSIONS AND WEIGHT</b>	
Transport width	10 ft. 10 in. (3.3 m)*
Operating width	16 ft. 4 in. (4.9 m)
Transport length	15 ft. 8 in. (4.8 m)
Operating length	15 ft. 3 in. (4.6 m)
Transport height	62 in. (1.6 m)
Operating height	62 in. (1.6 m)
Ground clearance w/header fully raised	11 in. (279 mm)
Shipping weight	3,035 lbs. (1379 kg)
Operating weight	2,610 lbs. (1186 kg)

\* With LH barrier folded down and RH door folded up.

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.



**SAFETY NEVER HURTS!™** Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.