

# 1200 SERIES EARLY RISER® PLANTER Specifications



## Models 1210, 1220 & 1230

PLANTER MODEL	MAINFRAME	DRIVE	DRIVE/CARRY WHEELS	PTO HP REQUIREMENTS	TRANSPORT HEIGHT**	TRANSPORT WIDTH**	ROW MARKERS	FERTILIZER/CAPACITY	ATTACHMENTS/OPTIONS
1210 6N Rigid Mounted 30 in. (762 mm)	7 x 7 in. (178 x 178 mm)	Heavy-duty, rear-mounted, 112-speed combination transmission; easy adjustment without tools	Goodyear Sure Grip 2 – 7.6 x 15SL, 10PR	—	9 ft. 10 in. (2.9 m)	19 ft. 4 in. (5.89 m)	Optional, Double-fold	NA	Chain guards, dual lift assist wheels, plus see Common Specifications List
1210 6N Rigid Mounted 36 in. (914 mm) 38 in. (965 mm) 40 in. (1016 mm)	7 x 7 in. (178 x 178 mm)	Heavy-duty, rear-mounted, 112-speed combination transmission; easy adjustment without tools	Goodyear Sure Grip 2 – 7.6 x 15SL, 10PR	—	9 ft. 4 in. (2.8 m)	6RW 36 in. – 20 ft. 11 in. (6.38 m) 6RW 38 in. – 21 ft. 9 in. (6.63 m) 6RW 40 in. – 22 ft. (6.71 m)	Optional, Double-fold	NA	Chain guards, dual lift assist wheels, plus see Common Specifications List
1210 8N Rigid Mounted 30 in. (762 mm)	7 x 7 in. (178 x 178 mm)	Heavy-duty, rear-mounted, 112-speed combination transmission; easy adjustment without tools	Goodyear Sure Grip 2 – 7.6 x 15SL, 10PR	150 PTO hp (105 w/assist)	9 ft. 4 in. (2.8 m)	24 ft. 4 in. (7.4 m)	Optional, Double-fold	NA	Chain guards, dual lift assist wheels, plus see Common Specifications List
1210 8W Rigid Mounted 36 in. (914 mm) 38 in. (965 mm) 40 in. (1016 mm)	7 x 7 in. (178 x 178 mm)	Heavy-duty, rear-mounted, 112-speed combination transmission; easy adjustment without tools	Goodyear Sure Grip 2 – 7.6 x 15SL, 10PR	150 PTO hp (105 w/assist)	11 ft. 4 in. (3.5 m)	8RW 36 in. – 26 ft. 11 in. (8.2 m) 8RW 38 in. – 28 ft. 1 in. (8.6 m) 8RW 40 in. – 28 ft. 8 in. (8.7 m)	Optional, Double-fold	NA	Chain guards, dual lift assist wheels, plus see Common Specifications List
1220 6N Trailing 30 in. (762 mm)	7 x 7 in. (178 x 178 mm)	Heavy-duty, rear-mounted, 112-speed combination transmission; easy adjustment without tools, Hydraulic seed drive with variable drive (opt.)	Goodyear Sure Grip 2 – 7.6 x 15, 10PR 4 – 7.6 x 15, 10PR w/fertilizer	75 PTO hp	11 ft. 2 in. (3.4 m)	17 ft. 3 in. (5.3 m)	Optional, Single-fold	Dry: 300 lb./row (136 kg) Liquid: 36.7 gal./row (139 L)	Chain and rock guards, plus see Common Specifications List
1220 8N Trailing 30 in. (762 mm)	7 x 7 in. (178 x 178 mm)	Heavy-duty, rear-mounted, 112-speed combination transmission; easy adjustment without tools, Hydraulic seed drive with variable drive (opt.)	Goodyear Sure Grip 4* – 7.6 x 15, 10PR	100 PTO hp	9 ft. 5 in. (2.9 m)	25 ft. (7.6 m)	Optional, Double-fold	Dry: 300 lb./row (136 kg) Liquid: 35 gal./row (132 L)	Chain and rock guards, plus see Common Specifications List
1230 8W Stackbar 38 in. (965 mm) 40 in. (1016 mm)	7 x 7 in. (178 x 178 mm)	Heavy-duty, rear-mounted, 112-speed combination transmission; easy adjustment without tools, Hydraulic seed drive with variable drive (opt.)	Goodyear Sure Grip 4* – 7.6 x 15SL, 10PR	150 PTO hp (105 w/assist)	11 ft. 2 in. (3.4 m)	8RW 36 in. – 16 ft. 10 in. (5.1 m) 8RW 38 in. – 17 ft. 6 in. (5.3 m) 8RW 40 in. – 17 ft. 6 in. (5.3 m)	Optional, Side-fold	NA	Chain guards, dual lift assist wheels, plus see Common Specifications List
1230 12N Stackbar 30 in. (762 mm)	7 x 7 in. (178 x 178 mm)	Heavy-duty, rear-mounted, 112-speed combination transmission; easy adjustment without tools, Hydraulic seed drive with variable drive (opt.)	Goodyear Sure Grip 4* – 7.6 x 15SL, 10PR	200 PTO hp (155 w/assist)	11 ft. 6 in. (3.5 m)	20 ft. 6 in. (6.3 m)	Optional, Side-fold	NA	Chain guards, dual lift assist wheels, plus see Common Specifications List

\* 2 drive; 2 carry \*\* With row markers

# 1200 SERIES EARLY RISER® PLANTER Specifications



## Models 1230 & 1240

PLANTER MODEL	MAINFRAME/ TOOLBAR	DRIVE	DRIVE/CARRY WHEELS	PTO HP REQUIREMENTS	TRANSPORT HEIGHT*	TRANSPORT WIDTH*	ROW MARKERS	FERTILIZER/ CAPACITY	ATTACHMENTS/ OPTIONS
1230 12W Stackerbar 36 in. (914 mm) 38 in. (965 mm) 40 in. (1016 mm)	7 x 7 in. (178 x 178 mm)	Heavy-duty, rear-mounted, 112-speed combination transmission; easy adjustment without tools, Hydraulic seed drive with variable drive (opt.)	Goodyear Sure Grip 4* – 7.6 x 15SL, 10PR	205 PTO hp (160 w/assist)	13 ft. 7 in. (4.1 m)	12RW 36 in. – 22 ft. (6.7 m) 12RW 38 in. – 22 ft. 5 in. (6.8 m) 12RW 40 in. – 22 ft. 5 in. (6.8 m)	Optional, Side-fold	NA	Chain guards, dual lift assist wheels, plus see Common Specifications List
1230 16N Stackerbar 30 in. (762 mm)	7 x 7 in. (178 x 178 mm)	3 heavy-duty, rear-mounted, 112-speed combination transmissions; easy adjustment without tools, Hydraulic seed drive with variable drive (opt.)	Goodyear Sure Grip 4 – 7.6 x 15SL, 10PR	185 PTO hp	13 ft. 9 in. (4.19 m)	26 ft. 10 in. (8.18 m)	Optional, Side-fold	NA	Chain guards, dual lift assist wheels (standard), plus see Common Specifications List
1240 12N Pivot-Transport 30 in. (762 mm)	8 x 8 in. (203 x 203 mm)/ 7 x 7 in. (178 x 178 mm)	2-section variable-rate hydraulic for seed and liquid fertilizer	Goodyear Farm Utility 2 – 7.6 x 15, 6PR Wings 4 – 16.5L x 16.1, 10PR Carry	140 PTO hp	10 ft. (3.1 m)	12 ft. 3 in. (3.7 m) 12 ft. 6 in. (3.8 m) w/fertilizer or bulk fill	Standard, Triple-fold	400 gal. (1514 L) planter-mounted or 600 gal. (2271 L) tractor-mounted	Bulk-fill seed, tractor-mounted liquid fertilizer, plus see Common Specifications List
1240 16N Pivot-Transport 30 in. (762 mm)	8 x 8 in. (203 x 203 mm)/ 7 x 7 in. (178 x 178 mm)	2-section variable-rate hydraulic for seed and liquid fertilizer	Goodyear Farm Utility 2 – 7.6 x 15, 6PR Wings 4 – 16.5L x 16.1, 10PR Carry	170 PTO hp	10 ft. (3.1 m)	12 ft. 3 in. (3.7 m) 12 ft. 6 in. (3.8 m) w/fertilizer or bulk fill	Standard, Triple-fold	460 gal. (1741 L) planter-mounted or 600 gal. (2271 L) tractor-mounted	Bulk-fill seed, tractor-mounted liquid fertilizer, plus see Common Specifications List
1240 12/23 Split-Row Pivot-Transport	8 x 8 in. (203 x 203 mm)/ 7 x 7 in. (178 x 178 mm)	4-section variable-rate hydraulic for seed and liquid fertilizer	Goodyear Farm Utility 2 – 7.6 x 15, 6PR Wings 4 – 16.5L x 16.1, 14PR Carry	210 PTO hp	10 ft. (3.1 m)	12 ft. 7 in. (3.8 m)	Standard, Triple-fold	600 gal. (2271 L) tractor-mounted	Tractor drawbar assist, rotary scrapers, plus see Common Specifications List
1240 16/31 Split-Row Pivot-Transport	8 x 8 in. (203 x 203 mm)/ 7 x 7 in. (178 x 178 mm)	4-section variable-rate hydraulic for seed and liquid fertilizer	Goodyear Farm Utility 2 – 7.6 x 15, 6PR Wings 4 – 16.5L x 16.1, 14PR Carry	240 PTO hp	10 ft. (3.1 m)	12 ft. 7 in. (3.8 m)	Standard, Triple-fold	600 gal. (2271 L) tractor-mounted	Tractor drawbar assist, rotary scrapers, plus see Common Specifications List
1240 24/20 Narrow-Row Pivot-Transport	8 x 8 in. (203 x 203 mm)/ 7 x 7 in. (178 x 178 mm)	4-section variable-rate hydraulic for seed and liquid fertilizer	Goodyear Farm Utility 2 – 7.6 x 15, 6PR Wings 4 – 16.5L x 16.1, 14PR Carry	240 PTO hp	10 ft. (3.1 m)	12 ft. 6 in. (3.8 m)	Standard, Triple-fold	600 gal. (2271 L) tractor-mounted	Tractor drawbar assist, rotary scrapers, plus see Common Specifications List

\* With row markers

### COMMON SPECIFICATIONS FOR RIGID MOUNTED, MOUNTED STACKERBAR AND TRAILING MODELS

#### Monitor System

Early Riser III (mounted & rigid trailing) Early Riser IV  
(mech. Drive 12 & 16 row) AFS Pro 600 color display

#### Attachments/Options

Granular chemical; Closed chemical systems; Row-mounted tillage attachments; Fertilizer; Fertilizer openers (not for rigid mounted and mounted stackerbar planters); PTO hydraulic pumps; Seed disks; Monitor installation kits; Vacuum fan case drain kits; Pneumatic row unit down pressure (12 row and larger).

# 1200 SERIES EARLY RISER® PLANTER Specifications



## Models 1250

PLANTER MODEL	MAINFRAME/ TOOLBAR	DRIVE	DRIVE/CARRY WHEELS	PTO HP REQUIREMENTS	TRANSPORT HEIGHT*	TRANSPORT WIDTH*	ROW MARKERS	FERTILIZER/ CAPACITY	ATTACHMENTS/ OPTIONS
1250 12N Front-Fold 30 in. (762 mm)	8 x 12 in. (203 x 305 mm)/ 6 x 10 in. (152 x 254 mm) inner telescoping frame	Hydraulic seed drive with variable rate (112-speed Mech. Drive opt.)	4 - 10 x 15 - Load Range D Highway Service Tires 2 - 10 x 15, 8PR Wings	150 PTO	11 ft. 1 in. (3.4 m)	11 ft. 11 in. (3.63 m)	Standard, Triple-fold	400 gal (1514 L) with On-Row Seed Hoppers, Tractor mounted tanks w/ Bulk-Fill Seed Hoppers	Bulk-fill seed, granular chemical, row mounted tillage attachments, 22 gpm PTO pump, rear towing hitch
1250 16N Front-Fold 30 in. (762 mm)	8 x 12 in. (203 x 305 mm)/ 6 x 10 in. (152 x 254 mm) inner telescoping frame	Hydraulic seed drive with variable rate (112-speed Mech. Drive opt.)	4 - 10 x 15 - Load Range D Highway Service Tires 4 - 10 x 15, 8PR Wings	180 PTO	11 ft. 1 in. (3.4 m)	11 ft. 11 in. (3.63 m)	Standard, Triple-fold	600 gal. (2271 L), with On-Row Seed Hoppers, Tractor mounted tanks w/ Bulk-Fill Seed Hoppers	Bulk-fill seed, 2 point hitch or drawbar hitch, granular chemical, row mounted tillage attachments, 22 gpm PTO pump, rear towing hitch
1250 24N Front-Fold 30 in. (762 mm)	8 x 16 in. (203 x 406 mm)/ 6 x 14 in. (152 x 355 mm) inner telescoping frame	Hydraulic seed drive with variable rate (112-speed Mech. Drive opt.)	4 - 11 x 22.5, 12PR 4 - 10 x 15, 8PR Wings (11 x 22.5, 12PR Opt.)	230 PTO	11 ft. 3 in. (3.43 m)	11 ft. 11 in. (3.63 m) - (12 ft. 3 in./3.73 m) with 11 x 22.5, 12 PR wing tires)	Standard, Triple-fold	600 gal. (2271 L), with On-Row Seed Hoppers or 400 gal. (1514 L) w/ Bulk-Fill Seed Hoppers	Bulk-fill seed, 2 point hitch or drawbar hitch, granular chemical, row mounted tillage attachments, 22 gpm PTO pump, rear towing hitch

\* With row markers

# 1200 SERIES EARLY RISER® PLANTER Specifications



## Model 1260

PLANTER MODEL	MAINFRAME/ TOOLBAR	DRIVE	CARRY WHEELS STD. / OPT.	PTO HP REQUIREMENTS*	TRANSPORT HEIGHT**	TRANSPORT WIDTH**	ROW MARKERS	FERTILIZER/ CAPACITY	ATTACHMENTS/OPTIONS
1260 32N Front-Fold 30 in. (762 mm)	8 x 16 in. (203 x 406 mm) outer w/ telescoping 6 x 14 in. (152 x 356 mm) inner tube w/ hydraulic hitch	Hydraulic Seed Drive w/ variable rate (4 sections)	425/65R22.5 Super Singles, walking tandems / 455/50R22.5, steerable axle	255 PTO	11 ft. 11 in. (3.63 m)	14 ft. 2 in. (4.31 m)	Optional, four section folding	600 gal. (2271 L) w/ Bulk-Fill Seed Hoppers, In-furrow Liquid Fertilizer	Granular chemical, Aux. shaft drive PTO pump, Row mount tillage tools, Steerable rear axle, Pneumatic row-unit down pressure, Seed disks, AFS Accu-Row Control
1260 36N Front-Fold 20 in. (508 mm)	8 x 16 in. (203 x 406 mm) outer w/ telescoping 6 x 14 in. (152 x 356 mm) inner tube w/ hydraulic hitch	Hydraulic Seed Drive w/ variable rate (2 sections)	425/65R22.5 Super Singles, walking tandems / 455/50R22.5, steerable axle	270 PTO	11 ft. 11 in. (3.63 m)	17 ft. 2 in. (5.23 m)	Optional, four section folding	600 gal. (2271 L) w/ Bulk-Fill Seed Hoppers, In-furrow Liquid Fertilizer	Granular chemical, Aux. shaft drive PTO pump, Row mount tillage tools, Steerable rear axle, Pneumatic row-unit down pressure, Seed disks, AFS Accu-Row Control
1260 36N Front-Fold 22 in. (559 mm)	8 x 16 in. (203 x 406 mm) outer w/ telescoping 6 x 14 in. (152 x 356 mm) inner tube w/ hydraulic hitch	Hydraulic Seed Drive w/ variable rate (2 sections)	425/65R22.5 Super Singles, walking tandems / 455/50R22.5, steerable axle	270 PTO	11 ft. 11 in. (3.63 m)	17 ft. 9 in. (5.41 m)	Optional, four section folding	600 gal. (2271 L) w/ Bulk-Fill Seed Hoppers, In-furrow Liquid Fertilizer	Granular chemical, Aux. shaft drive PTO pump, Row mount tillage tools, Steerable rear axle, Pneumatic row-unit down pressure, Seed disks, AFS Accu-Row Control
1260 36N Front-Fold 30 in. (762 mm)	8 x 16 in. (203 x 406 mm) outer w/ telescoping 6 x 14 in. (152 x 356 mm) inner tube w/ hydraulic hitch	Hydraulic Seed Drive w/ variable rate (4 sections)	425/65R22.5 Super Singles, walking tandems / 455/50R22.5, steerable axle	270 PTO	11 ft. 11 in. (3.63 m)	14 ft. 2 in. (4.31 m)	Optional, four section folding	600 gal. (2271 L) w/ Bulk-Fill Seed Hoppers, In-furrow Liquid Fertilizer	Granular chemical, Aux. shaft drive PTO pump, Row mount tillage tools, Steerable rear axle, Pneumatic row-unit down pressure, Seed disks, AFS Accu-Row Control

\* Min. PTO HP requirements @ 5 mph, add +30HP/MPH planting speed increase.

\*\* With markers

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.



**SAFETY NEVER HURTS!™** Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.