

FLEXIBILITY

Available in a wide range of row spacings:

- 32- & 36-row 30 in. spacing
- 36-row 20 in. spacing
- 36-row 22 in. spacing

STABILITY

Wing wheels also serve as transport wheels for minimal tongue weight and maximum transport stability.



MANEUVERABILITY

Exclusive rear steerable axle provides outstanding maneuverability when entering tight field approaches.



EARLY RISER® – BETTER STANDS FOR HIGHER YIELDS

When it comes to large frame planters, Case IH engineers listened. You told us that maneuverability, frame flexibility and transport stability are important for

planters of this size. Case IH delivered with the new 1260 Early Riser planter, offering exclusive features like a steerable rear axle and castering wing gauge wheels that

remain on the ground during transport. New features that make the Case IH 1260 planter more maneuverable than planters half it's size.

MODEL	32 ROW 30 IN. SPACING	36 ROW 30 IN. SPACING	36 ROW 20 IN. SPACING	36 ROW 22 IN. SPACING
GENERAL				
Frame type	Trailing, Front Fold			
Number of rows	32	36	36	36
Wing flex points	6R-7R-6R-7R-6R	6R-9R-6R-9R-6R	13R-10R-13R	13R-10R-13R
Wing flex angle	Outer: ±20°; Inner: ±15°			±20°
Row spacing	Narrow: 30 in. (762 mm)		Narrow: 20 in. (508 mm)	Narrow: 22 in. (559 mm)
Seed metering	Vacuum			
SEED CAPACITY				
Seed tanks	Twin, 60 bu. (2114 L) bulk-fill			
OVERALL				
Mainframe	8 x 16 in. (203 x 406 mm) outer w/ telescoping 6 x 14 in. (152 x 356 mm) inner tube w/ hydraulic hitch			
Wings	12 X 12 in. (305 x 305 mm)			
Drive	Hydraulic Seed Drive w/ variable rate (4 sections)		Hydraulic Seed Drive w/ variable rate (2 sections)	
Carrying wheels – std./opt.	425/65R22.5 Super Singles, walking tandems / 455/50R22.5, steerable axle			
Wing wheels	4 – 12.5L X 15 walking tandems		2 – 12.5L X 15 walking tandems	
Hitch	Drawbar hitch			
Hydraulic markers	Optional Four Section Folding, 16 in. (406 mm) smooth disk blade, shear bolt protection, adjustable disk angle			
Monitor/Controller	AFS Pro 600 color touchscreen display			
Transport weight - w/ fert.	43,560 lb. (19 758 kg) empty	45,800 lb. (20 755 kg) empty	36,350 lb. (16 488 kg) empty	36,960 lb. (16 765 kg) empty
Transport drawbar weight (empty)	2,240 lb. (1016 kg)	2,360 lb. (1070 kg)	3,020 lb. (1370 kg)	3,240 lb. (1470 kg)
Min. PTO HP requirements @ 5 mph*	255 PTO HP	270 PTO HP	270 PTO HP	270 PTO HP
DIMENSIONS				
Transport height w/markers	11 ft. 11 in. (3.63 m)	11 ft. 11 in. (3.63 m)	11 ft. 11 in. (3.63 m)	11 ft. 11 in. (3.63 m)
Transport width w/markers	14 ft. 2 in. (4.31 m)	14 ft. 2 in. (4.31 m)	17 ft. 2 in. (5.23 m)	17 ft. 9 in. (5.41 m)
Transport length	51 ft. 5 in. (15.67 m)	56 ft. 5 in. (17.2 m)	43 ft. 2 in. (13.16 m)	44 ft. 9 in. (13.64 m)
Transport: Hitch to carrier wheels	41 ft. 5 in. (12.62 m)	46 ft. 5 in. (14.14 m)	33 ft. 2 in. (10.11 m)	34 ft. 8 in. (10.57 m)
ATTACHMENTS AND OPTIONS				
Granular chemical, Aux. shaft drive PTO pump, Row mount tillage tools, In-furrow liquid fert. w/ 600 gal. tank, Steerable rear axle, Pneumatic row-unit down pressure, Seed disks, AFS Accu-Row Control				

* +30HP/MPH planting speed increase



Safety Never Hurts!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.

Case IH is a registered trademark of CNH America LLC.

Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.

Availability of some models and equipment builds vary according to the country in which the equipment is used.