

FLEX-TILL 600 CHISEL PLOW Specifications



Model Flex-Till 600

9 IN. (229 MM) SPACING*																		
Number of shanks	35	37	43	45	47	49	51	53	55	57	59	61	63	65	71	73	79	81
	3-Section Models										5-Section Models							
Working width – ft. (m)	26' 3" (8.0)	27' 9" (8.5)	32' 3" (9.8)	33' 9" (10.3)	35' 3" (10.8)	36' 9" (11.2)	38' 3" (11.7)	39' 9" (12.1)	41' 3" (12.6)	42' 9" (13.0)	44' 3" (13.5)	45' 9" (13.9)	47' 3" (14.4)	48' 9" (14.9)	53' 3" (16.3)	54' 9" (16.7)	59' 3" (18.0)	60' 9" (18.5)
Transport width – ft. (m)	18' 8" (5.7)	18' 8" (5.7)	18' 6" (5.6)	18' 6" (5.6)	21' 8" (6.6)	21' 8" (6.6)	18' 8" (5.7)	18' 8" (5.7)	21' 8" (6.6)	21' 8" (6.6)	18' 8" (5.7)	18' 8" (5.7)	21' 8" (6.6)	21' 8" (6.6)	21' 8" (6.6)	21' 8" (6.6)	21' 8" (6.6)	21' 8" (6.6)
Transport height – ft. (m)	12' 6" (3.8)	12' 6" (3.8)	15' 2" (4.6)	15' 2" (4.6)	15' 2" (4.6)	15' 2" (4.6)	17' 11" (5.5)	17' 11" (5.5)	17' 11" (5.5)	17' 11" (5.5)	13' 10" (4.2)	13' 10" (4.2)	13' 10" (4.2)	13' 10" (4.2)	16' 10" (5.1)	16' 10" (5.1)	16' 10" (5.1)	16' 10" (5.1)
Overall length – ft. (m)	25' 4" (7.7)	25' 4" (7.7)	25' 4" (7.7)	25' 4" (7.7)	26' 2" (8.0)	26' 2" (8.0)	25' 4" (7.7)	25' 4" (7.7)	26' 2" (8.0)	26' 2" (8.0)	26' 2" (8.0)	24' 4" (7.4)	26' 2" (8.0)	26' 2" (8.0)	26' 2" (8.0)	26' 2" (8.0)	26' 2" (8.0)	26' 2" (8.0)
Total weight – lbs. (kg)	11,648 (5283)	11,881 (5389)	12,913 (5857)	13,177 (5977)	13,567 (6154)	13,831 (6274)	14,782 (6705)	15,046 (6825)	15,478 (7021)	15,742 (7141)	18,351 (8324)	18,584 (8430)	19,096 (8662)	19,329 (8768)	20,874 (9468)	21,107 (9574)	22,222 (10080)	22,486 (10200)
Center frame width – ft. (m)	13' (3.96)	13' (3.96)	13' (3.96)	13' (3.96)	16' (4.88)	16' (4.88)	13' (3.96)	13' (3.96)	16' (4.88)	16' (4.88)	13' (3.96)	13' (3.96)	16' (4.88)	16' (4.88)	16' (4.88)	16' (4.88)	16' (4.88)	16' (4.88)
Inner wing width – ft. (m)	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	9' (2.74)	9' (2.74)	9' (2.74)	9' (2.74)	12' (3.66)	12' (3.66)	12' (3.66)	12' (3.66)
Outer wing width – ft. (m)	6' (1.83)	6' (1.83)	9' (2.74)	9' (2.74)	9' (2.74)	9' (2.74)	12' (3.66)	12' (3.66)	12' (3.66)	12' (3.66)	6' (1.83)	6' (1.83)	6' (1.83)	6' (1.83)	6' (1.83)	6' (1.83)	9' (2.74)	9' (2.74)

* Dimensions include 12 in. (305 mm) sweeps on 9 in. (229 mm) shank spacing. Weights based on 550 lb (160 kg) trips and do not include ground engaging tools or harrows.

12 IN. (305 MM) SPACING**																		
Number of shanks	27	29	33	35	36	38	39	41	42	44	45	47	48	50	54	56	60	62
	3-Section Models										5-Section Models							
Working width – ft. (m)	27' 0" (8.2)	29' 0" (8.8)	33' 0" (10.1)	35' 0" (10.7)	36' 0" (10.9)	38' 0" (11.6)	39' 0" (11.9)	41' 0" (12.5)	42' 0" (12.8)	44' 0" (13.4)	45' 0" (13.7)	47' 0" (14.3)	48' 0" (14.6)	50' 0" (15.2)	54' 0" (16.5)	56' 0" (17.1)	60' 0" (18.3)	62' 0" (18.9)
Transport width – ft. (m)	18' 8" (5.7)	18' 8" (5.7)	18' 6" (5.6)	18' 6" (5.6)	21' 8" (6.6)	21' 8" (6.6)	18' 8" (5.7)	18' 8" (5.7)	21' 8" (6.6)	21' 8" (6.6)	18' 8" (5.7)	18' 8" (5.7)	21' 8" (6.6)	21' 8" (6.6)	21' 8" (6.6)	21' 8" (6.6)	21' 8" (6.6)	21' 8" (6.6)
Transport height – ft. (m)	12' 6" (3.8)	12' 6" (3.8)	15' 2" (4.6)	15' 2" (4.6)	15' 2" (4.6)	15' 2" (4.6)	17' 11" (5.5)	17' 11" (5.5)	17' 11" (5.5)	17' 11" (5.5)	13' 10" (4.2)	13' 10" (4.2)	13' 10" (4.2)	13' 10" (4.2)	16' 10" (5.1)	16' 10" (5.1)	16' 10" (5.1)	16' 10" (5.1)
Overall length – ft. (m)	25' 4" (7.7)	25' 4" (7.7)	25' 4" (7.7)	25' 4" (7.7)	26' 2" (8.0)	26' 2" (8.0)	25' 4" (7.7)	25' 4" (7.7)	26' 2" (8.0)	26' 2" (8.0)	24' 4" (7.4)	25' 4" (7.7)	26' 2" (8.0)	26' 2" (8.0)	26' 2" (8.0)	26' 2" (8.0)	26' 2" (8.0)	26' 2" (8.0)
Total weight – lbs. (kg)	11,145 (5055)	11,417 (5179)	12,400 (5625)	12,686 (5754)	13,002 (5898)	13,288 (6027)	14,037 (6367)	14,323 (6497)	14,682 (6660)	14,967 (6789)	17,443 (7912)	17,715 (8035)	18,136 (8226)	18,408 (8350)	19,669 (8922)	19,941 (9045)	21,007 (9529)	21,293 (9658)
Center frame width – ft. (m)	13' (3.96)	13' (3.96)	13' (3.96)	13' (3.96)	16' (4.88)	16' (4.88)	13' (3.96)	13' (3.96)	16' (4.88)	16' (4.88)	13' (3.96)	13' (3.96)	16' (4.88)	16' (4.88)	16' (4.88)	16' (4.88)	16' (4.88)	16' (4.88)
Inner wing width – ft. (m)	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	9' (2.74)	9' (2.74)	9' (2.74)	9' (2.74)	12' (3.66)	12' (3.66)	12' (3.66)	12' (3.66)
Outer wing width – ft. (m)	6' (1.83)	6' (1.83)	9' (2.74)	9' (2.74)	9' (2.74)	9' (2.74)	12' (3.66)	12' (3.66)	12' (3.66)	12' (3.66)	6' (1.83)	6' (1.83)	6' (1.83)	6' (1.83)	6' (1.83)	6' (1.83)	9' (2.74)	9' (2.74)

** Dimensions include 16 in. (410 mm) sweeps on 12 in. (305 mm) shank spacing. Weights based on 650 lb (160 kg) trips and do not include ground engaging tools or harrows.

TRIPS AND SHANKS	TIRES	CENTER TIRES	OPTIONS
550 lb. (250 kg), 1 x 2 in. (25.4 x 50.8 mm) shanks, 2.25 in. (57.1 mm) centers fit 50", 9 in. (229 mm) spacing 650 lb. (295 kg), 1.25 x 2 in. (31.7 x 50.8 mm) shanks, 2.25 in. (57.1 mm) centers fit 50", 12 in. (305 mm) spacing	3-section models: 12 tires 5-section models: 18 tires	9" (229 mm) spacing, 35-53 shank, 3-section models: 11L x 15 (D) 9" (229 mm) spacing, 55 & 57 shank, 3-section models: 11L x 15 (F) 9" (229 mm) spacing, 5-section models: 235/75R x 17.5 (H) 12" (305 mm) spacing, 27-38 shank, 3-section models: 11L x 15 (D) 12" (305 mm) spacing, 39 & 44 shank, 3-section models: 11L x 15 (F) 12" (305 mm) spacing, 5-section models: 235/75R x 17.5 (H)	Mudscrapers Trip shim kits Rear hitch for towing implements Air package Mounted press wheels Ground engaging tools Work switches Mounted harrows Endmarkers Tine furrow closer

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

© 2008 CNH America LLC. All rights reserved. www.caseih.com/na

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.



SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.