

FARMALL® C SERIES TRACTOR Specifications



Models Farmall 65C, Farmall 75C, Farmall 85C & Farmall 95C

	Farmall 65C	Farmall 75C	Farmall 85C	Farmall 95C
ENGINE¹				
Gross Engine Horsepower	64 hp (48 kW)	76 hp (57 kW)	84 hp (63 kW)	95 hp (71 kW)
PTO Horsepower	50 hp (37 kW)	62 hp (46 kW)	70 hp (52 kW)	80 hp (60 kW)
Rated Speed (RPM)	2300	2300	2300	2300
Maximum Torque RPM	1400	1400	1400	1400
PTO Torque Rise	46%	39%	39%	35%
Number of Cylinders	4	4	4	4
Aspiration	Turbocharged & intercooled	Turbocharged & intercooled	Turbocharged & intercooled	Turbocharged & intercooled
Displacement	195 cu. in. (3.2 L)	195 cu. in. (3.2 L)	274 cu. in. (4.5 L)	274 cu. in. (4.5 L)
Starting Aid	Thermostart	Thermostart	Air intake grid heater	Air intake grid heater
FUEL SYSTEM				
Fuel Injection	Direct, mechanical governor	Direct, mechanical governor	Direct, mechanical governor	Direct, mechanical governor
Injection Pump	Bosch VE	Bosch VE	Bosch VE	Bosch VE
TRANSMISSION				
Standard	16x16 with mechanical shuttle	16x16 with mechanical shuttle	16x16 with mechanical shuttle	16x16 with mechanical shuttle
Optional	16x16 with power shuttle	16x16 with power shuttle	16x16 with power shuttle	16x16 with power shuttle
Differential Lock	Mechanical engagement	Mechanical engagement	Mechanical engagement	Mechanical engagement
Brakes	Hydraulic wet disc	Hydraulic wet disc	Hydraulic wet disc	Hydraulic wet disc
Transport Speed*	19 mph (30 kph), 25 mph (40 kph) optional w/MFD	19 mph (30 kph), 25 mph (40 kph) optional w/MFD	19 mph (30 kph), 25 mph (40 kph) optional w/MFD	25 mph (40 kph)
HYDRAULICS & HITCH				
Hydraulic System	Open center	Open center	Open center	Open center
System Pressure	2,755 psi (190 bar)	2,755 psi (190 bar)	2,755 psi (190 bar)	2,755 psi (190 bar)
Steering and Services Pump – gpm (L/min)	7.4 (28) or 9.4 (35) w/high flow opt.	7.4 (28) or 9.4 (35) w/high flow opt.	9.4 (35)	9.4 (35)
Implement Pump – gpm (L/min)	12.8 (48) or 16.9 (64) w/high flow opt. or cab	12.8 (48) or 16.9 (64) w/high flow opt. or cab	15.0 (57)	15.0 (57)
Rear Remote Valves	1 standard; up to 4 optional	1 standard; up to 4 optional	1 standard; up to 4 optional	1 standard; up to 4 optional
Optional Mid-mount Loader Valve	Open center, joystick controlled	Open center, joystick controlled	Open center, joystick controlled	Open center, joystick controlled
Steering Type	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Hitch Category	II convertible to I Telescopic Stabilizers & Flexible Link Ends	II convertible to I Telescopic Stabilizers & Flexible Link Ends	II convertible to I Telescopic Stabilizers & Flexible Link Ends	II convertible to I Telescopic Stabilizers & Flexible Link Ends
Sensing Type	Mechanical, lower link	Mechanical, lower link	Mechanical, lower link	Mechanical, lower link
Hitch Lift Capacity (SAE) max.	3,960 lb. (1796 kg)	3,960 lb. (1796 kg)	3,960 lb. (1796 kg)	3,960 lb. (1796 kg)
PTO				
Type	Independent, dry clutch	Independent, dry clutch	Independent, dry clutch	Independent, dry clutch
Engagement	Mechanical, servo-assist	Mechanical, servo-assist	Mechanical, servo-assist	Mechanical, servo-assist
Speeds	540	540	540	540
CAPACITIES				
Fuel Capacity	19.8 gal. (75 L)	19.8 gal. (75 L)	23.2 gal. (88 L)	23.2 gal. (88 L)
Alternator Amps (ROPS/Cab)	120	120	120	120
Battery Capacity (cold cranking amps)	730	730	730	730
APPROXIMATE DIMENSIONS**				
Wheelbase (2WD/MFD)	83.9 in. (2131 mm) / 81.3 in. (2065 mm)	83.9 in. (2131 mm) / 81.3 in. (2065 mm)	NA / 86.0 in. (2185 mm)	NA / 86.0 in. (2185 mm)
Overall Length (2WD/MFD)	155.7 in. (3954 mm) / 154 in. (3912 mm)	155.7 in. (3954 mm) / 154 in. (3912 mm)	NA / 157 in. (3987 mm)	NA / 157 in. (3987 mm)
Overall Width (min./max.)	69.6 in. (1768 mm) / 93.1 in. (2365 mm)	69.6 in. (1768 mm) / 93.1 in. (2365 mm)	69.6 in. (1768 mm) / 93.1 in. (2365 mm)	69.6 in. (1768 mm) / 93.1 in. (2365 mm)
Height to top of ROPS (down/up)	75.6 in. (1920 mm) / 95.6 in. (2428 mm)	75.6 in. (1920 mm) / 95.6 in. (2428 mm)	75.6 in. (1920 mm) / 95.6 in. (2428 mm)	75.6 in. (1920 mm) / 95.6 in. (2428 mm)
Height to top of Cab	91.5 in. (2324 mm)	91.5 in. (2324 mm)	91.5 in. (2324 mm)	91.5 in. (2324 mm)
APPROXIMATE WEIGHT				
2WD (ROPS/Cab)	5,148 lb. (2335 kg) / 5,588 lb. (2535 kg)	5,148 lb. (2335 kg) / 5,588 lb. (2535 kg)	NA	NA
MFD (ROPS/Cab)	5,632 lb. (2555 kg) / 6,063 lb. (2750 kg)	5,632 lb. (2555 kg) / 6,063 lb. (2750 kg)	6,074 lb. (2755 kg) / 6,504 lb. (2950 kg)	6,074 lb. (2755 kg) / 6,504 lb. (2950 kg)

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

© 2008 CNH America LLC. All rights reserved. www.caseih.com/na

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.



SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.