

FARMALL® SERIES TRACTOR Specifications



Models Farmall 70, Farmall 80, Farmall 90 & Farmall 95

SPECIFICATIONS	Farmall 70	Farmall 80	Farmall 90	Farmall 95
POWER				
Gross Engine Horespower	65	72	84	90
PTO Horsepower	52	62	70	80
Rated Speed (RPM)	2500	2500	2300	2500
Number of Cylinders / Aspiration	4 / Turbocharged & Intercooled	4 / Turbocharged & Intercooled	4 / Turbocharged & Intercooled	4 / Turbocharged & Intercooled
Emissionization standard	Tier-III	Tier-III	Tier-III	Tier-III
Displacement	238 (3.9L)	238 (3.9L)	274 (4.5L)	274 (4.5L)
Starting Aid	Thermostart	Thermostart	Thermostart	Thermostart
Air Filter	Dry / Duel Element	Dry / Duel Element	Dry / Duel Element	Dry / Duel Element
TRANSMISSION				
Standard	12 X 12 with Mechanical Shuttle	12 X 12 with Mechanical Shuttle	12 X 12 with Mechanical Shuttle	12 X 12 with Mechanical Shuttle
Optional	20 X 12 Creeper with Mechanical Shuttle	20 X 12 Creeper with Mechanical Shuttle	20 X 12 Creeper with Mechanical Shuttle	20 X 12 Creeper with Mechanical Shuttle
Rear Differential Lock	Mechanical	Mechanical	Mechanical	Mechanical
Brakes	Hydraulic actuated wet disk	Hydraulic actuated wet disk	Hydraulic actuated wet disk	Hydraulic actuated wet disk
PLATFORM				
Type	Flat Deck	Flat Deck	Flat Deck	Flat Deck
FUEL SYSTEM				
Fuel Injection	Direct, w/Mechanical Governor	Direct, w/Mechanical Governor	Direct, w/Mechanical Governor	Direct, w/Mechanical Governor
HYDRAULICS & HITCH				
Hydraulic System	Open Center	Open Center	Open Center	Open Center
Implement Pump	13.6 GPM	13.6 GPM	13.6 GPM	13.6 GPM
Steering & Services Pump	8.1 GPM	8.1 GPM	8.1 GPM	8.1 GPM
Total Tractor Flow	21.7 GPM	21.7 GPM	21.7 GPM	21.7 GPM
Rear Remote Valves	One open center remote valve STD	One open center remote valve STD	One open center remote valve STD	One open center remote valve STD
Optional Mid-Mount Loader Valve	Available with Loader	Available with Loader	Available with Loader	Available with Loader
Hitch Category	Category II	Category II	Category II	Category II
Sensing Type	Mechanical	Mechanical	Mechanical	Mechanical
Hitch List Capacity @ 24 in. lbs. (ASAE)	4,010 lb.	5,025 lb	5,025 lb	5,025 lb
Link Ends	Fixed	Fixed	Fixed	Fixed
Optional Link Ends	Yes	Yes	Yes	Yes
PTO				
Type	Independent dry clutch	Independent dry clutch	Independent dry clutch	Independent dry clutch
Engagement	Mechanical	Mechanical	Mechanical	Mechanical
Speeds	540 RPM	540 RPM	540 RPM	540 RPM
Optional 540/1000 RPM	No	No	No	Yes
CAPACITIES				
Fuel Capacity	23.8 gal. (90.1 l)	23.8 gal. (90.1 l)	23.8 gal. (90.1 l)	23.8 gal. (90.1 l)
Alternator Amps	12 volt, 85 amp	12 volt, 85 amp	12 volt, 85 amp	12 volt, 85 amp
Battery Capacity (Cold Cranking Amps)	800	800	800	800
Approx Weight (lbs.) - ROPS 2WD / MFD	5,152 / 5,704	5,702 / 6,254	5,702 / 6,254	6,107 / 6,659
Approx Weight (lbs.) - CAB 2WD / MFD	5,813 / 6,365	6,363 / 6,915	6,363 / 6,915	6,768 / 7,320
APPROXIMATE DIMENSIONS				
Height to top of ROPS	97 in. (2464 mm)	101.1 in. (2568 mm)	101.1 in. (2568 mm) *	101.1 in. (2568 mm) *
Height to top of CAB	100 in. (2540 mm)	103.1 in. (2619 mm)	103.1 in. (2619 mm) *	103.1 in. (2619 mm) *
Wheelbase - 2WD	86 in. (2184 mm)	91 in. (2311 mm)	91 in. (2311 mm)	94 in. (2387 mm)
Wheelbase - MFD	84 in. (2133 mm)	87 in. (2209 mm)	87 in. (2209 mm)	92 in. (2336 mm)

* 18.4 X 30 Rear Tires

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.



SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.