



## TRACTORS

Model	Displacement	PTO HP	Gross Engine HP	Power Boost	Power Growth
-------	--------------	--------	-----------------	-------------	--------------

### Steiger Tractors

335	543 cu. in. (9 L)	273 hp (204 kW)	335 hp (250 kW)	NA	33 hp (25 kW)
385	787 cu. in. (12.9 L)	339 hp (253 kW)	385 hp (287 kW)	NA	38 hp (28 kW)
435	787 cu. in. (12.9 L)	379 hp (282 kW)	435 hp (325 kW)	NA	43 hp (32 kW)
485	787 cu. in. (12.9 L)	429 hp (320 kW)	485 hp (362 kW)	NA	49 hp (37 kW)
535	915 cu. in. (15 L)	473 hp (352 kW)	535 hp (399 kW)	NA	54 hp (40 kW)
535 Pro	915 cu. in. (15 L)	473 hp (352 kW)	535 hp (399 kW)	35 hp (26 kW)	54 hp (40 kW)

### Magnum Tractors

215	505 cu. in. (8.3 L)	175 hp (131 kW)	221 hp (165 kW)	NA	38 hp (28 kW)
245	505 cu. in. (8.3 L)	200 hp (149 kW)	248 hp (185 kW)	NA	40 hp (30 kW)
275	543 cu. in. (9 L)	225 hp (168 kW)	275 hp (205 kW)	NA	40 hp (30 kW)
305	543 cu. in. (9 L)	255 hp (190 kW)	304 hp (227 kW)	NA	41 hp (31 kW)
335	543 cu. in. (9 L)	275 hp (205 kW)	330 hp (246 kW)	NA	36 hp (27 kW)

### Puma Tractors

115	411 cu. in. (6.75 L)	95 hp (70 kW)	115 hp (86 kW)	25 hp (18 kW)	11 hp (8 kW)
125	411 cu. in. (6.75 L)	105 hp (78 kW)	125 hp (93 kW)	25 hp (18 kW)	11 hp (8 kW)
140	411 cu. in. (6.75 L)	120 hp (89 kW)	140 hp (104 kW)	25 hp (18 kW)	11 hp (8 kW)
155	411 cu. in. (6.75 L)	135 hp (101 kW)	155 hp (116 kW)	10 hp (7 kW)	11 hp (8 kW)
165	411 cu. in. (6.75 L)	135 hp (101 kW)	165 hp (123 kW)	35 hp (26 kW)	23 hp (17 kW)
180	411 cu. in. (6.75 L)	150 hp (112 kW)	180 hp (134 kW)	35 hp (26 kW)	21 hp (15 kW)
195	411 cu. in. (6.75 L)	165 hp (123 kW)	195 hp (145 kW)	35 hp (26 kW)	18 hp (13 kW)
210	411 cu. in. (6.75 L)	180 hp (134 kW)	210 hp (157 kW)	25 hp (19 kW)	13 hp (9 kW)

### Maxxum Tractors

110	274 cu. in. (4.5 L)	90 hp (67 kW)	110 hp (82 kW)	NA	NA
110 Pro	274 cu. in. (4.5 L)	90 hp (67 kW)	110 hp (82 kW)	20 hp (15 kW)	11 hp (8 kW)
115	411 cu. in. (6.75 L)	95 hp (71 kW)	115 hp (86 kW)	NA	NA
120 Pro	274 cu. in. (4.5 L)	100 hp (75 kW)	120 hp (90 kW)	19 hp (14 kW)	11 hp (8 kW)
125	411 cu. in. (6.75 L)	105 hp (78 kW)	125 hp (93 kW)	NA	NA
125 Pro	411 cu. in. (6.75 L)	105 hp (78 kW)	125 hp (93 kW)	25 hp (19 kW)	11 hp (8 kW)
130 Pro	274 cu. in. (4.5 L)	110 hp (82 kW)	130 hp (97 kW)	9 hp (7 kW)	11 hp (8 kW)
140 Pro	411 cu. in. (6.75 L)	120 hp (90 kW)	140 hp (104 kW)	25 hp (19 kW)	11 hp (8 kW)

## TRACTORS

Model	Displacement	PTO HP	Gross Engine HP
-------	--------------	--------	-----------------

### Farmall U Series Tractors

Farmall 85U	274 cu. in. (4.5 L)	70 hp (52 kW)	85 hp (63 kW)
Farmall 95U	274 cu. in. (4.5 L)	80 hp (60 kW)	95 hp (71 kW)
Farmall 105U	274 cu. in. (4.5 L)	90 hp (67 kW)	105 hp (78 kW)

### Farmall Series Tractors

Farmall 70	238 cu. in. (3.9 L)	52 hp (39 kW)	65 hp (47 kW)
Farmall 80	238 cu. in. (3.9L)	62 hp (46 kW)	72 hp (52 kW)
Farmall 90	274 cu. in. (4.5L)	70 hp (52 kW)	84 hp (61 kW)
Farmall 95	274 cu. in. (4.5L)	80 hp (60 kW)	95 hp (70 kW)

### JXN Series Tractors

JX1075N	179 cu. in. (2.9 L)	62 hp (46.2 kW)	75 hp (55.9 kW)
JX1095N	238 cu. in. (3.9 L)	80 hp (59.7 kW)	91 hp (67.9 kW)

### Farmall C Series Tractors

Farmall 65C	195 cu. in. (3.2L)	50 hp (37 kW)	64 hp (48 kW)
Farmall 75C	195 cu. in. (3.2L)	62 hp (46 kW)	76 hp (57 kW)
Farmall 85C	274 cu. in. (4.5L)	70 hp (52 kW)	84 hp (63 kW)
Farmall 95C	274 cu. in. (4.5 L)	80 hp (60 kW)	95 hp (71 kW)

### Farmall Compact Series Tractors

Farmall 31	91.3 cu. in. (1.5 L)	26.5 hp (18.6 kW)	31 hp (23.1 kW)
Farmall 35	101.4 cu. in. (1.7 L)	28.9 hp (21.6 kW)	35 hp (26.1 kW)
Farmall 40	121.7 cu. in. (2.0 L)	35 hp (26.1 kW)	40 hp (29.9 kW)
Farmall 45	135.2 cu. in. (2.2 L)	39.6 hp (29.6 kW)	45 hp (33.6 kW)
Farmall 50	135.2 cu. in. (2.2 L)	43 hp (32.1 kW)	50 hp (37.3 kW)
Farmall 55	135.2 cu. in. (2.2 L)	47 hp (35 kW)	55 hp (41 kW)
Farmall 60	135.2 cu. in. (2.2 L)	51 hp (38 kW)	60 hp (44.8 kW)

## SOIL PREPARATION

Model	Working Width	Shanks	Shank Spacing
-------	---------------	--------	---------------

### Mulch Till Rippers

ecolo-tiger 9300	22 ft. 6 in. (6.9 m)	9	30 in. (762 mm)
ecolo-tiger 730C	17 ft. 6 in. (5.3 m)	7	30 in. (762 mm)
ecolo-tiger 530C	12 ft. 6 in. (3.8 m)	5	30 in. (762 mm)
ecolo-tiger 527B	11 ft. 3 in. (3.4 m)	5	
MRX690 or Conser-Till 690	12 ft. 6 in. or 17 ft. 6 in. (3.8 or 5.3 m)	5 or 7 Front/rear disks 12/14 or 18/20	30 in. (762 mm) Disk Spacing 12 in. (305 mm)

### In-Line Rippers

ecolo-till 2500	7 ft. 6 in. to 26 ft. 6 in. (2.3 to 8.1 m)	NA	30, 36, 38 or 40 in. (762, 914, 965, or 1016 mm)
2500 Rip Strip	4-, 6-, or 8-row (30, 36, 38, or 40 in. spacing)	NA	30, 36, 38 or 40 in. (762, 914, 965, or 1016 mm)

### Chisel Plow

Flex-Till 600	26 ft. 3 in. to 62 ft. 0 in. (8.0 to 18.9 m)	27 to 81	9 & 12 in. (229 & 305 mm)
---------------	--	----------	---------------------------

### Field Cultivator

Model	Working Width
tiger-mate II®/200 Field Cultivators	18 to 60 ft. (4.87 to 18.2 m)

### Soil Conditioners

Model	Working Width
crumbler 110 Seed Bed Finisher	12.5 to 50 ft. (3.8 to 15.2 m)
crumbler 160 Soil Finisher (P/T)	15 to 25 ft. (4.6 to 7.6 m)

### Disk Harrows

Model	Working Width
True-Tandem Disk Harrows (340/370)	19 to 34 ft. (5.8 to 10.4 m)
Heavy-Offset 790 Disk Harrow	10 to 27 ft. (3.05 to 8.23 m)

Model	Tillage Width	Transport Width	Working Speed
-------	---------------	-----------------	---------------

### True-Tandem 330 Turbo

25 ft. (7.62 m)	24 ft. 7 in. (3.4 m)	15 ft 9 in. (4.8 m)	Up to 7-9 mph (5-7 hp/ft.)
34 ft. (10.36 m)	34 ft. 1 in. (10.4 m)	17 ft 10 in. (5.4 m)	Up to 7-9 mph (5-7 hp/ft.)

## PLANTING & SEEDING

Model	Tow Position	Bins	Bin Split	Capacity
-------	--------------	------	-----------	----------

### Air Systems

Precision Air 2230	Between/Behind	2	86/144 bu. (3030/5074 L)	230 bu. (8105 L)
Precision Air 2280	Between/Behind	2	169/118 bu. (5955/4158 L)	280 bu. (10 113 L)
Precision Air 2330	Between/Behind	2	186/142 bu. (6554/5004 L)	330 bu. (11 558 L)
Precision Air 3380	Between/Behind	3	169/93/118 bu. (5955/3277/4158 L)	380 bu. (13 390 L)
Precision Air 3430	Between/Behind	3	186/102/142 bu. (6554/3594/5004 L)	430 bu. (15 153 L)

Model	Width	Row Sections	Row Spacings
-------	-------	--------------	--------------

### Air Hoe Drills

Flex Hoe 400	27 ft. (8.2 m)	3	7.2, 10 or 12 in. (19, 25.4 or 30.5 cm)
	33 ft. (10.1 m)	3	7.2, 10 or 12 in. (19, 25.4 or 30.5 cm)
	39 ft. (11.9 m)	3	7.2, 10 or 12 in. (19, 25.4 or 30.5 cm)
	45 ft. (13.7 m)	5	7.2, 10 or 12 in. (19, 25.4 or 30.5 cm)
Flex Hoe 700	51 ft. (15.5 m)	5	7.2, 10 or 12 in. (19, 25.4 or 30.5 cm)
	60 ft. (18.3 m)	5	7.5, 10 or 12 in. (19, 25.4 or 30.5 cm)
	70 ft. (21.3 m)	5	10 or 12 in. (25.4 or 30.5 cm)

### Single Disk No-Till Air Drills

Precision Disk 30	30 ft. (9.1 m)	NA	7.5 or 10 in. (19 or 25.4 cm)
Precision Disk 40	40 ft (12.2 m)	NA	7.5, 10, 15 in. (19, 25.4 or 38.1 cm)

Type	Configuration
------	---------------

### Early Riser® Planters

Trailing Rigid	6 & 8 row narrow
Trailing Pivot-Transport	12 & 16 row narrow, 24 row/20 in.
Trailing Pivot-Transport Split-Row	12/23 & 16/31 split-row
Trailing Front Fold	12, 16 & 24 row narrow
Mounted Stackerbar	12 & 16 row narrow, 8 & 12 row wide
Mounted Rigid	6 & 8 row narrow, 6 & 8 row wide

# SPECIFICATIONS

## CROP APPLICATION

Model	Engine HP	Tank Size	Boom Length	Ground Clearance	Wheel Track Adjustment
-------	-----------	-----------	-------------	------------------	------------------------

### Patriot™ Sprayers

3150	152 hp (113.4 kW)	750 gal. (2838 L)	75 ft. (22.9 m) or 90 ft. (27.4 m) self-centering	48 in. (122 cm)	120-152 in. (305-386 cm)
3185	185 hp (138 kW)	750 gal. (2838 L)	75 ft. (22.9 m) or 90 ft. (27.4 m) self-centering	50 in. (127 cm) or 58 in. (147 cm)	120-152 in. (305-386 cm)
3320	235 hp (175 kW)	1000 gal. (3785 L)	60/90 ft. (18.3/27.4 m); 60/100 ft. (18.3/30.5 m) self-centering	52 in. (132 cm)	120-157 in. (305-399 cm)
3330	250 HP (186 kW)	1000 gal. (3785 L)	60/90 ft. (18.3/27.4 m); 60/100 ft. (18.3/30.5 m); or 60/90/120 ft. (18.3/27.4/36.6 m) self-centering	52 in. (132 cm)	120-157 in. (305-399 cm)
4420	290 hp (216 kW)	1200 gal. (4542 L)	60/90 ft. (18.3/27.4 m); 60/100 ft. (18.3/30.5 m); or 60/90/120 ft. (18.3/27.4/36.6 m) self-centering	53 in. (135 cm)	120-157 in. (305-399 cm)

Model	Engine HP	Peak HP	Model	Box/Tank Size	Boom
-------	-----------	---------	-------	---------------	------

### Titan™ Floaters

3020	305 hp (227.4 kW)	340 hp (253.5 kW)
3520	365 hp (272.2 kW)	380 hp (283.4 kW)
4020	305 hp (227.4 kW)	340 hp (253.5 kW)
4520	365 hp (272.2 kW)	380 hp (283.4 kW)

### Application Systems for Floater Chassis

810 Flex-Air	287 cu. ft. single bin	60, 70 ft.
	346 cu. ft. double bin	
	346 cu. ft. triple bin	
610 Liquid System	1,800 or 2,000 gal.	70, 60/85 ft.

Model	Tank Size	Boom Type	Boom Length
-------	-----------	-----------	-------------

### Pull Type Sprayers

Precision Spray 100	1,000 gal.	Suspended Boom	80, 90, 100 ft. (24.4, 27.4, 30.5 m)
Precision Spray 100/160	1,600 gal.	Suspended Boom	80, 90, 100, 120, 126, 134 ft. (24.4, 27.4, 30.5, 36.6, 38.4, 40.8 m)
Precision Spray 160	1,600 gal.	Wheel Boom	80, 84, 90, 94, 100, 104, 110, 114, 120, 124, 130 or 134 ft. (24.4, 25.6, 27.4, 28.6, 30.5, 31.7, 33.5, 34.7, 36.6, 37.8, 39.6 or 40.8 m)

Model	Frame	Coulters/Rows (30 in. spacing)	Working Width
-------	-------	-----------------------------------	---------------

### Fertilizer Placement Equipment

NPX2800 (850 or 1000 gal.)	Pull-type	7, 9, or 11 coulters	17 ft. 6 in. - 27 ft. 6 in. (5.3 - 8.4 m)
NPX2800 (1,300 gal.)	Pull-type	11, 13, or 15 coulters	27 ft. 6 in. - 37 ft. 6 in. (8.4 - 11.4 m)
NPX5300 Applicator	Mounted	—	20 ft. 0 in. - 37 ft. 6 in. (6.1 - 11.4 m)
NPX5300 Applicator	Single fold	—	27 ft. 6 in. - 37 ft. 6 in. (8.4 - 11.4 m)
	Double fold	—	40 ft. 0 in. - 52 ft. 6 in. (12.2 - 16 m)
NTX5310 Strip-Till System	Mounted	6 or 8 row	15 ft. or 20 ft. (4.6 or 6.1 m)
	Pull-type	8, 12, or 16 row	20, 30, or 40 ft. (6.1, 9.1, or 12.2 m)

## HAY & FORAGE

Model	Bale size	Bale Diameter/Length	PTO RPM/Min. PTO HP
-------	-----------	----------------------	---------------------

### RB 4 Series Round Balers

RB444	3.9 ft. (1.2 m)	2.5-4 ft. (0.76-1.2 m)	540/40 hp (30 kW)
RB454	3.9 ft. (1.2 m)	3-5 ft. (0.9-1.5 m)	540/60 hp (45 kW)
Silage	3.9 ft. (1.2 m)	3-5 ft. (0.9-1.5 m)	540/65 hp (48 kW)
Rotor Cutter	3.9 ft. (1.2 m)	3-5 ft. (0.9-1.5 m)	540/100 hp (75 kW)
RB464	3.9 ft. (1.2 m)	3-6 ft. (0.9-1.8 m)	540/70 hp (52 kW)
RB554	5.1 ft. (1.6 m)	3-5 ft. (0.9-1.5 m)	540/70 hp (52 kW)
RB564	5.1 ft. (1.6 m)	3-6 ft. (0.9-1.8 m)	540 or 1000/80 hp (60 kW)

### LB 3 Series Large Square Balers

LB333 Standard	2.7 x 2.9 ft. (0.8 x 0.9 m)	3.9-9.0 ft. (1.2-2.75 m)	1000/102 hp (75 kW)
Packer Cutter	2.7 x 2.9 ft. (0.8 x 0.9 m)	3.9-9.0 ft. (1.2-2.75 m)	1000/110 hp (80 kW)
Rotor Cutter	2.7 x 2.9 ft. (0.8 x 0.9 m)	3.9-9.0 ft. (1.2-2.75 m)	1000/130 hp (95 kW)
LB433 Standard	3.9 x 2.9 ft. (1.2 x 0.9 m)	3.9-9.0 ft. (1.2-2.75 m)	1000/122 hp (90 kW)
Rotor Cutter	3.9 x 2.9 ft. (1.2 x 0.9 m)	3.9-9.0 ft. (1.2-2.75 m)	1000/150 hp (110 kW)

### SB 1 Small Square Balers

SB521	14 x 18 in. (0.36 x 0.46 m)	1.0-4.3 ft. (0.31-1.3 m)	540/35 hp (26 kW)
SB531	14 x 18 in. (0.36 x 0.46 m)	1.0-4.3 ft. (0.31-1.3 m)	540/62 hp (45 kW)
SB541	14 x 18 in. (0.36 x 0.46 m)	1.0-4.3 ft. (0.31-1.3 m)	540/75 hp (56 kW)
SB551	16 x 18 in. (0.41 x 0.46 m)	1.0-4.3 ft. (0.31-1.3 m)	540/80 hp (60 kW)

Model	Engine Displacement	Rated Horsepower	Working Speed Range
-------	---------------------	------------------	---------------------

### WD "3" Series Self-Propelled Windrowers

WD1203	274 cu. in. (4.5 L)	126 hp (94 kW) @ 2,300 rpm	0-10.3 mph (0-16.6 kph)
WD1903	456 cu. in. (7.5 L)	190 hp (142 kW) @ 2,100 rpm	0-11 mph (0-17.8 kph)
WD2303	456 cu. in. (7.5 L)	226 hp (168 kW) @ 2,100 rpm	0-11 mph (0-17.8 kph)

Model	Type	Discs	Cutting Width	Cutting Height	PTO Req'd
-------	------	-------	---------------	----------------	-----------

### Rotary Disc Mower Conditioners

DC92	Side Pull	7	9 ft. 2 in. (2.8 m)	0.95-3.25 in. (24-83 mm)	65 hp (48 kW)
DC102	Side Pull	8	10 ft. 4 in. (3.2 m)	0.95-3.25 in. (24-83 mm)	80 hp (60 kW)
DC132	Center Pivot	10	13 ft. 0 in. (4.0 m)	0.95-3.25 in. (24-83 mm)	90 hp (67 kW)
DC162	Center Pivot	12	15 ft. 7 in. (4.7 m)	0.95-3.25 in. (24-83 mm)	100 hp (75 kW)

## MATERIAL HANDLING

Model	Net HP	Operating Load	Bucket height @ pin
-------	--------	----------------	---------------------

### 400 Series 3 Skid Steer Loaders

410	57 hp (42 kW)	1,500 lb. (681 kg)	114.9 in. (2.92 m)
420	69 hp (51 kW)	1,750 lb. (794 kg)	120.7 in. (3.06 m)
430	77 hp (57 kW)	2,000 lb. (907 kg)	121.6 in. (3.09 m)
440	83 hp (62 kW)	2,200 lb. (998 kg)	121.6 in. (3.09 m)
435	77 hp (57 kW)	2,300 lb. (1043 kg)	120 in. (3.04 m)
445	77 hp (57 kW)	2,500 lb. (1134 kg)	122.4 in. (3.11 m)
450	83 hp (62 kW)	2,450 lb. (1111 kg)	124.5 in. (3.16 m)
465	83 hp (62 kW)	3,000 lb. (1361 kg)	125.5 in. (3.19 m)

### 400 Series 3 Compact Track Loaders

420CT	69 hp (51 kW)	2,000 lb. (907 kg)	120.8 in. (3.07 m)
440CT	83 hp (62 kW)	2,100 lb. (952 kg)	121.7 in. (3.09 m)
445CT	77 hp (57 kW)	2,310 lb. (1098 kg)	122.4 in. (3.11 m)
450CT	83 hp (62 kW)	2,700 lb. (1225 kg)	124.8 in. (3.17 m)

# SPECIFICATIONS

HARVESTING					
Model	Rated Engine HP	Maximum HP	Grain Tank Capacity	Unloading Speed	Cleaning System Size

## Axial-Flow Combines

5088	265 hp (198 kW)	290 hp (216 kW)	250 bu. (8810 L)	2.5 bu./sec.	7,947 sq. in. (5.1 m <sup>3</sup> )
6088	305 hp (227 kW)	330 hp (246 kW)	300 bu. (10 570 L)	3.0 bu./sec.	7,947 sq. in. (5.1 m <sup>3</sup> )
7088	325 hp (242 kW)	375 hp (280 kW)	300 bu. (10 570 L)	3.0 bu./sec.	7,947 sq. in. (5.1 m <sup>3</sup> )
7120	360 hp (268 kW)	415 hp (309 kW)	315 bu. (11 100 L)	3.2 bu./sec.	8,370 sq. in. (5.4 m <sup>3</sup> )
8120	420 hp (313 kW)	463 hp (345 kW)	350 bu. (12 330 L)	3.2 bu./sec.	10,075 sq. in. (6.5 m <sup>3</sup> )

Model	Engine HP	Displacement	Rows	Chamber/Basket Capacity	Picking Speed
-------	-----------	--------------	------	-------------------------	---------------

## Module Express & Cotton Express Pickers

420	260 hp (194 kW)	505 cu. in. (8.3 L)	4 or 5	8,500 lb. (3856 kg)	0 to 4.8 mph (up to 7.7 kph)
620	365 hp (272 kW)	550 cu. in. (9.0 L)	4 or 6	10,500 lb. (4762 kg)	0 to 4.8 mph (up to 7.7 kph)
625	365 hp (272 kW)	550 cu. in. (9.0 L)	4 or 6	4,000-12,000 lbs. (1816-5448 kg)	0 to 4.8 mph (up to 7.7 kph)

HARVESTING			
Model	Combine Compatibility	Header Type/ # of Rows	Cutting Widths/Row Spacing

## Axial-Flow Grain Headers

1010	2500 Series	Rigid Auger	20, 25, 30 ft. (6.1, 7.62, 9.14 m)
1020	2500 Series	Flexible Auger	20, 22.5, 25, 30 ft. (6.1, 6.9, 7.62, 9.14 m)
2010	88 & 20 Series	Rigid Auger	20, 25, 30 ft. (6.1, 7.62, 9.14 m)
2020	88 & 20 Series	Flexible Auger	20, 25, 30, 35 ft. (6.1, 7.62, 9.14, 11.67 m)
2142	All Combines	Rigid Draper	25, 30, 35 ft. (7.62, 9.14, 10.6 m)
2152	All Combines	Rigid Draper	25, 30, 35, 40, 45 ft. (7.62, 9.14, 10.6, 12.2, 14.8 m)
2162	All Combines	Flexible Draper	30, 35, 40 ft. (9.14, 10.6, 12.2 m)

## Axial-Flow Corn Heads

3206	2500 Series	6	30, 36, 38 in. (762, 914, 965 mm)
3208	2500 Series	8	22, 30, 36, 38 in. (559, 762, 914, 965 mm)
3212	2588	12	20, 22, 30 in. (508, 559, 762 mm)
3406	88 Series	6	30, 36, 38 in. (762, 914, 965 mm)
3408	88 & 20 Series	8	22, 30, 36, 38 in. (559, 762, 914, 965 mm)
3412	88 & 20 Series	12	20, 22, 30 in. (508, 559, 762 mm)
2606	2500 & 88 Series	6	30 in. (762 mm)
2608	All Combines	8	30 in. (762 mm)
2608F	All Combines	8	30 in. (762 mm)
2612	20 Series	12	30 in. (762 mm)

## Axial-Flow Pick-Up Heads

2015	2577 & 2588	Pick-up	14 ft. (4.27 m)
2016	88 & 20 Series	Pick-up	14, 16 ft. (4.27, 4.87 m)

FARMALL ATTACHMENTS	
Model	Description
L Series Loaders	Lift capacities from 1,250-2,500 lb. (568-1135 kg) at bucket pivot point
MW Series Mid-mount Mowers	60, 72 & 84 in. (152, 183 & 213 cm) cutting width
BS Series Snowblowers	2-stage, front- and rear-mounted models
BR Series Rotary Brooms	60 & 72 in. (152 & 193 cm) widths
BM Series Front Blades	72 & 84 in. (183 & 213 cm) widths
BH Series Backhoes	Digging depths from 72-114 in. (183-290 cm)
TL Series Rotary Tillers	52, 60, 72 & 80 in. (132, 152, 183 & 203 cm) widths
RR Series Rear-mounted Mowers	60, 72, & 90 in. (152, 183, & 229 cm) Cat. I, 3-pt. hitch
RR Series Flex Wing Mowers	12, 15, & 17 ft. (3.66, 4.57, & 5.18 m) Cat. I, 3-pt. hitch
Ballast Boxes	400 & 1,825 lb. (182 & 829 kg) capacity, 3-pt. mounted

L700 SERIES LOADERS			
Loader Model	Tractor Model	Max. Lift Capacity @ Max. Height @ Pins	Max. Lift Height
L720	JXC1060C-JX1095C; Farmall 65C-95C	3,300 lbs. (1497)	124 in. (3.15 m)
	JX60-80; Farmall 90-95	3,300 lbs. (1497)	125 in. (3.17 m)
	JX1080U-JX1100U; Farmall 85U-105U 2WD	3,300 lbs. (1497)	125 in. (3.17 m)
L730	JX1085C-JX1095C; Farmall 85C-95C	3,850 lbs. (1746 kg)	133 in. (3.37 m)
	JX1080U-JX1100U; Farmall 85U-105U	3,850 lbs. (1746 kg)	136 in. (3.45 m)
	JX75-95; Farmall 90-95	3,850 lbs. (1746 kg)	136 in. (3.45 m)
L740	JX1090U-1100U; Farmall 85U-105U	3,850 lbs. (1746 kg)	136 in. (3.45 m)
	Maxxum 110	4,750 lbs. (2155 kg)	144 in. (3.65 m)
	Maxxum 110, 120, 130 Pro	5,080 lbs. (2304 kg)	145 in. (3.68 m)
L750	Maxxum 115, 125	5,000 lbs. (2268 kg)	154 in. (3.91 kg)
	Maxxum 125, 140 Pro	5,350 lbs. (2427 kg)	154 in. (3.91 kg)
L760	Puma 115-155	6,050 lbs. (2744 kg)	169 in. (4.29 m)
L770	Puma 165-210	5,450 lbs (2472 kg)	178 in. (4.52 m)
L780	Magnum 215-335	5,950 lbs. (2699 kg)	187 in. (4.74 m)

**SAFETY NEVER HURTS!™** Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

Case IH is a registered trademark of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

**CASE IH. FOR THOSE WHO DEMAND MORE.™**